



Material Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: 3M™ ESPE™ IMPRINT™ 4 PRELIMINARY Super Quick Economy Pack
MANUFACTURER: 3M
DIVISION: 3M ESPE Dental Products
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 10/14/14
Supersedes Date: Initial Issue
Document Group: 34-0693-1

ID Number(s):

70-2011-4254-7

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

33-4241-7, 33-4256-5

No revision information is available.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	33-4241-7	Version Number:	3.01
Issue Date:	08/17/21	Supersedes Date:	03/20/20

SECTION 1: Identification

1.1. Product identifier

3M™ Imprint™ 4 Preliminary Super Quick Base

Product Identification Numbers

LE-F100-1572-2

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression Material

Restrictions on use

For use only by dental professionals.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Oral Care Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

12% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	68855-54-9	20 - 40 Trade Secret *
POLY(DIMETHYLSILOXANE)	63148-62-9	10 - 30 Trade Secret *
VINYL-POLYDIMETHYL SILOXANE	68083-19-2	10 - 30 Trade Secret *
DIMETHYL METHYL HYDROGEN SILICONE FLUID	68037-59-2	1 - 20 Trade Secret *
Siloxanes and Silicones, di-Me, mono(vinyl group)-terminated	68952-00-1	1 - 20 Trade Secret *
Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material	None	1 - 20 Trade Secret *
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	68611-44-9	1 - 10 Trade Secret *
Titanium Dioxide	13463-67-7	< 1 Trade Secret *
Mentha arvensis, ext.	90063-97-1	< 0.2 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

No need for first aid is anticipated.

Skin Contact:

No need for first aid is anticipated.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m ³	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m ³	
SILICA, AMORPHOUS	68611-44-9	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m ³	
CAS NO SEQ117921	68855-54-9	ACGIH	TWA(inhalable particulates):10 mg/m ³	
CAS NO SEQ117922	68855-54-9	ACGIH	TWA(respirable particles):3	

			mg/m3	
DUST, INERT OR NUISANCE	68855-54-9	OSHA	TWA(as total dust):15 mg/m3;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):5 mg/m3;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3)	
SILICA, AMORPHOUS	68855-54-9	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Solid

Color

White

Specific Physical Form:

Paste

Odor

Minty

Odor threshold

No Data Available

pH

Not Applicable

Melting point

Not Applicable

Boiling Point

Not Applicable

Flash Point

No flash point

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Classified

Flammable Limits(LEL)

Not Applicable

Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>No Data Available</i>
Vapor Density	<i>No Data Available</i>
Density	1.2 - 1.4 g/cm ³
Specific Gravity	1.2 - 1.4 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Volatile Organic Compounds	<i>Not Applicable</i>
Percent volatile	<i>Not Applicable</i>
VOC Less H ₂ O & Exempt Solvents	<i>Not Applicable</i>

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions. This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Amines
Strong acids
Strong bases
Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured

product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.7 mg/l
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Ingestion	Rat	LD50 > 2,000 mg/kg
POLY(DIMETHYLSILOXANE)	Dermal	Rabbit	LD50 > 19,400 mg/kg
POLY(DIMETHYLSILOXANE)	Ingestion	Rat	LD50 > 17,000 mg/kg
VINYL-POLYDIMETHYL SILOXANE	Dermal	Rabbit	LD50 > 15,440 mg/kg
VINYL-POLYDIMETHYL SILOXANE	Ingestion	Rat	LD50 > 15,440 mg/kg
DIMETHYL METHYL HYDROGEN SILICONE FLUID	Dermal	Rabbit	LD50 > 2,000 mg/kg
DIMETHYL METHYL HYDROGEN SILICONE FLUID	Ingestion	Rat	LD50 > 2,000 mg/kg
Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material	Ingestion		LD50 estimated to be > 5,000 mg/kg
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l

DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Mentha arvensis, ext.	Dermal	Rabbit	LD50 > 5,000 mg/kg
Mentha arvensis, ext.	Ingestion	Rat	LD50 1,240 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	In vitro data	No significant irritation
POLY(DIMETHYLSILOXANE)	Rabbit	No significant irritation
VINYL-POLYDIMETHYL SILOXANE	Rabbit	No significant irritation
DIMETHYL METHYL HYDROGEN SILICONE FLUID	Rabbit	No significant irritation
Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material		No significant irritation
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Mentha arvensis, ext.	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Rabbit	Mild irritant
POLY(DIMETHYLSILOXANE)	Rabbit	No significant irritation
VINYL-POLYDIMETHYL SILOXANE	Rabbit	Mild irritant
DIMETHYL METHYL HYDROGEN SILICONE FLUID	Rabbit	Mild irritant
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Mentha arvensis, ext.	In vitro data	Severe irritant

Skin Sensitization

Name	Species	Value
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Mouse	Not classified
DIMETHYL METHYL HYDROGEN SILICONE FLUID	Guinea pig	Not classified
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Human and animal	Not classified
Titanium Dioxide	Human and animal	Not classified
Mentha arvensis, ext.	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	In Vitro	Some positive data exist, but the data are not sufficient for classification
DIMETHYL METHYL HYDROGEN SILICONE FLUID	In Vitro	Not mutagenic
Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-	In vivo	Some positive data exist, but the data are not

terminated (CAS 104780-78-1), bulk material		sufficient for classification
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation	Human and animal	Carcinogenic
Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material	Inhalation	Human and animal	Carcinogenic
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Ingestion	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 3,738 mg/kg/day	90 days
Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Not applicable

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 0 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	33-4241-7	Version Number:	3.01
Issue Date:	08/17/21	Supersedes Date:	03/20/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	33-4256-5	Version Number:	3.00
Issue Date:	03/20/20	Supersedes Date:	02/25/16

SECTION 1: Identification

1.1. Product identifier

3M™ Imprint™ 4 Preliminary Super Quick Catalyst

Product Identification Numbers

LE-F100-1573-3

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression Material

Restrictions on use

For use only by dental professionals.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Oral Care Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

24% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	68855-54-9	10 - 30 Trade Secret *
VINYL-POLYDIMETHYLSILOXANE	68083-19-2	10 - 30 Trade Secret *
Siloxanes and Silicones, di-Me, mono(vinyl group)-terminated	68952-00-1	10 - 25 Trade Secret *
SODIUM ALUMINUM SILICATE	37244-96-5	10 - 25 Trade Secret *
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	68611-44-9	1 - 20 Trade Secret *
POLY(DIMETHYLSILOXANE)	63148-62-9	1 - 20 Trade Secret *
Titanium Dioxide	13463-67-7	< 1.0 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Observe precautions from other sections. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
SILICA, AMORPHOUS	68611-44-9	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	
Cristobalite	68855-54-9	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.

Cristobalite	68855-54-9	OSHA	TWA concentration(respirable):0.05 mg/m3(1.2 millions of particles/cu. ft.);TWA:0.05 mg/m3	
SILICA, AMORPHOUS	68855-54-9	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Solid

Color

Pink

Specific Physical Form:

Paste

Odor

Slight Odor, Characteristic Odor

Odor threshold

No Data Available

pH

No Data Available

Melting point

No Data Available

Boiling Point

No Data Available

Flash Point

No flash point

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Classified

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Density	1.2 g/cm ³ - 1.4 g/cm ³
Specific Gravity	1.2 - 1.4 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	No Data Available
Volatile Organic Compounds	Not Applicable
Percent volatile	Not Applicable
VOC Less H ₂ O & Exempt Solvents	Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Amines
Strong acids
Strong bases
Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTALLINE AIRRESP	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYSTALLINE AIRRESP	68855-54-9	Known human carcinogen	National Toxicology Program Carcinogens
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.7 mg/l
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Ingestion	Rat	LD50 > 2,000 mg/kg
VINYL-POLYDIMETHYLSILOXANE	Dermal	Rabbit	LD50 > 15,440 mg/kg
VINYL-POLYDIMETHYLSILOXANE	Ingestion	Rat	LD50 > 15,440 mg/kg
SODIUM ALUMINUM SILICATE	Dermal		LD50 estimated to be > 5,000 mg/kg
SODIUM ALUMINUM SILICATE	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
POLY(DIMETHYLSILOXANE)	Dermal	Rabbit	LD50 > 19,400 mg/kg
POLY(DIMETHYLSILOXANE)	Ingestion	Rat	LD50 > 17,000 mg/kg
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg

Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	In vitro data	No significant irritation
VINYL-POLYDIMETHYLSILOXANE	Rabbit	No significant irritation
SODIUM ALUMINUM SILICATE	Professional judgement	No significant irritation
POLY(DIMETHYLSILOXANE)	Rabbit	No significant irritation
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Rabbit	Mild irritant
VINYL-POLYDIMETHYLSILOXANE	Rabbit	Mild irritant
SODIUM ALUMINUM SILICATE	Professional judgement	Mild irritant
POLY(DIMETHYLSILOXANE)	Rabbit	No significant irritation
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Mouse	Not classified
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Human and animal	Not classified
Titanium Dioxide	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	In Vitro	Some positive data exist, but the data are not sufficient for classification
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation	Human and animal	Carcinogenic
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Flux calcined diatomaceous earth (cristobalite 1 - <10%)	Ingestion	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 3,738 mg/kg/day	90 days
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Not applicable

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification**Health:** 0 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	33-4256-5	Version Number:	3.00
Issue Date:	03/20/20	Supersedes Date:	02/25/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com